

Loresta-GXII MCP-T710

Accurate resistivity measurement using the reliable
4-pin probe method

Loresta-GXII

Low resistivity meter, Measuring range $10^{-4} \sim 10^7 \Omega$

Expanded Measuring Range and Useful Functions
Functional 7.5-inch color LCD Touch-Screen



- Expanded measuring range, $10^{-4} \sim 10^7 \Omega$
- Silicon Mode for silicon wafer measurement
- One-touch automatic measurement by new functions, Auto-hold and Timer Mode
- Real-time output of measurement results

Standard accessories



ASR Probe
RMH501



ASR Probe checker
RMH304

*Probes for Loresta GX cannot be connected to Loresta GXII

Nittoseiko Analytech Co., Ltd.

Loresta-GX II

(MCP-T710)

- Accurate Low Resistivity Meter based on 4 Terminal 4 Pin Method
- One-touch measurement by dedicated probe on Ω , Ω/\square , $\Omega\cdot\text{cm}$ and S/cm
- Operation on Touch-Screen, RCF setting, Measurement, Data Save, Data Output and Data Management

Accurate and quick measurement of materials' resistivity

4 Terminal 4 Pin Method

- High accuracy with eliminating contact resistance between sample and probe and lead wire's resistance
- Dedicated probe with spring contact method keeps constant pin pitch, pressure and contact area on samples



● Probe should be placed perpendicularly on samples.

Uses

■ Production engineering ■ Quality control ■ R & D

Applications

- Conductive paint, Conductive ink, Conductive paste, Resistive paste (carbon etc.), Conductive plastics, Conductive rubber, Silicon wafer
- Conductive films, Transparent conductive films, ITO Glass, Metal evaporated films, Sprayed metal layers, Sheet metals, Antistatic materials, Electromagnetic shield materials, Conductive fiber, Conductive ceramics, etc.
- Plating, Magnesium alloy, Surface treatment, etc.

Features

- Expanded measuring range: $0.001 \times 10^{-4} \sim 9.999 \times 10^7 \Omega$
- One-touch operation: Automatic measurement with functional Auto-hold and Timer Mode
- Silicon Mode for silicon wafer measurement
- Low conductive materials are acceptable by Selectable Applied Current Function
- Current polarity reversing makes stable measurement
- Real-time output of measurement results to a PC (using data logger software sold separately)

Specifications

- Method: 4 Terminal 4 Pin Method
- Measurement mode: Auto-hold
- Mode: Measurement end by value's stability.
- Timer Mode: Measurement end by set time
- Display: 640x480dots, 7.5 inch full-color TFT-LCD touch screen
- Data output: USB flash drive, Serial (USB B)
- Power source: AC85~264V 47~63Hz, 40VA
- Dimensions, weight: W320 x D285 x H110mm, Lid opened H200mm, approx. 2.4kg
- Standard accessory: ASR probe RMH501 and Probe checker RMH304

*Specifications and appearance are subject to change without prior notice.



● Check the probe with Probe Checker prior to measurement.

		Supply current							
		1A	100mA	10mA	1mA	100 μ A	10 μ A	1 μ A	0.1 μ A
Range	10^{-4}	$\pm (2.0\% + 30\text{dgt})$							
	10^{-3}	$\pm (2.0\% + 20\text{dgt})$	$\pm (2.0\% + 20\text{dgt})$						
	10^{-2}	$\pm (1.0\% + 5\text{dgt})$	$\pm (1.0\% + 5\text{dgt})$	$\pm (2.0\% + 20\text{dgt})$					
	10^{-1}	$\pm (1.0\% + 3\text{dgt})$	$\pm (1.0\% + 3\text{dgt})$	$\pm (1.0\% + 5\text{dgt})$	$\pm (2.0\% + 20\text{dgt})$				
	10^0		$\pm (0.5\% + 3\text{dgt})$	$\pm (0.5\% + 3\text{dgt})$	$\pm (1.0\% + 5\text{dgt})$	$\pm (2.0\% + 20\text{dgt})$			
	10^1			$\pm (0.5\% + 3\text{dgt})$	$\pm (0.5\% + 3\text{dgt})$	$\pm (1.0\% + 5\text{dgt})$	$\pm (2.0\% + 20\text{dgt})$		
	10^2				$\pm (0.5\% + 3\text{dgt})$	$\pm (0.5\% + 3\text{dgt})$	$\pm (1.0\% + 5\text{dgt})$	$\pm (2.0\% + 20\text{dgt})$	
	10^3					$\pm (0.5\% + 3\text{dgt})$	$\pm (0.5\% + 3\text{dgt})$	$\pm (1.0\% + 5\text{dgt})$	$\pm (2.0\% + 20\text{dgt})$
	10^4						$\pm (0.5\% + 3\text{dgt})$	$\pm (0.5\% + 3\text{dgt})$	$\pm (1.0\% + 5\text{dgt})$
	10^5							$\pm (0.5\% + 3\text{dgt})$	$\pm (1.0\% + 3\text{dgt})$
	10^6								$\pm (1.0\% + 3\text{dgt})$
	10^7								$\pm (2.0\% + 5\text{dgt})$

Options

*Probes for Loresta GX cannot be connected to Loresta GXII

● ESR



RMH502

For non-uniform samples
Pin pitch 5mm
Pin point's diameter
2mm x 4pins
Spring pressure 230g/pin

● LSR



RMH503

For soft surface samples
Pin pitch 5mm
Pin top hemisphere
2mm x 4pins
Spring pressure 140g/pin


● PSR



RMH504

For small samples
Pin pitch 1.5mm
Pin points 0.26R x 4pins
Spring pressure 95g/pin

● QR



RMH505

For very small samples
Pin pitch 1.5mm
Pin points 0.26R x 4pins
Pin arrangement Square
Spring pressure 95g/pin

● BSR



RMH506

For very large samples
Pin pitch 2.5mm
Pin points 0.37R x 4pins
Spring pressure 170g/pin

● NSCR



RMH507

For Silicon Wafer
Pin pitch 1.0mm
Pin points 0.04R x 4pins
Spring pressure 250g/pin

Note:

Follow instructions in manuals to correctly install, connect and operate the instruments. Contents of catalogues are subject to change without prior notice when improvements are made in performance. The actual color of the goods may appear different from color printed. All screen images are simulated.

*Company and product names contained herein are the trademarks or registered trademarks of the company concerned.

Nittoseiko Analytech Co., Ltd.

7-10-1 Chuo-rinkan, Yamato, Kanagawa 242-0007, JAPAN

Tel: +81(0)46-278-0056

URL: <https://www.n-analytech.co.jp/global>



Sintech Scientific (S.E.A.) Pte Ltd

No. 194 Pandan Loop #04-11

Pantech Business Hub

Singapore 128383

Tel: 65-67790007

Fax: 63520877, 63520885

Email: sales@sintechscientific.com

Website: www.sintechscientific.com

CAT No.29080223081E