

MAP-PAK

2

O₂ and CO₂ Gas Analysers for Modified Atmosphere Packaging

V1.2
11/12/24

Accurate Analysis of Gas Flushed Food Packaging

Following on from the success of the original Map-Pak analyser, the Map-Pak 2 is the fifth generation of analysers from AGC Instruments designed specifically for the Food Industry. It has been completely re-designed with a new large colour Touch Screen, Lithium Battery, and Large SD memory to drive an easy-to-use User Interface. With a faster CO₂ sensor complimenting the industry-leading O₂ sensor, the Map-Pak 2 gas analyser swiftly and precisely measures the O₂ and O₂ / CO₂ content of gas flushed food packaging (Modified Atmosphere Packaging).

1. The **Map-Pak 2 Combi** measures the Oxygen, Carbon Dioxide and Nitrogen content in gas flushed food packages (the latter being as a balance gas).
2. The **Map-Pak 2 O2** measures the Oxygen content in gas flushed food packages.

The Map-Pak 2 was developed as a quality control device with a wide range of features which can be used with minimal training. As a result, this analyser provides a key analytical solution to cover your food packaging quality control requirements. The easily programmable 'Product Profile' feature incorporates all the important information and control features required and is comprised of the following editable parameters for each product:

- Customer Name
- Product Name
- Weight
- O₂ and CO₂ Alarms (High & Low)
- Gas Volume Setting
- CO₂ Response Setting for improved accuracy

These lightweight portable analysers are easy to use in quality control functions and can be used for all food applications, as well as some applications in the pharmaceutical industry. Sample measurements and results are achieved within 20 seconds and the operator can modify the various features of the analyser to best suit their requirements. A minimal gas sample is required, and three sample volume options are available to suit all packaging types. A long battery life also ensures continuous operations in busy production schedules.

The probe holder has now been integrated into the unit for ease of use and storage as well as safely covering the needle when not in use. Strengthened and wipe-clean materials are used in an ergonomic design for weight reduction and increased comfort for the operator. There are also features such as the new internal Filter and external Hydrophobic Filter to protect the analyser sensor array which saves on maintenance costs. The new modular probe also allows for the easy replacement of parts by the end user. Furthermore, no software is required to download the results to a PC which is done via the dual-use USB cable provided for charging and data transfer.




Features

- 3.5" Colour Touch Screen Display
- Measurement range of 0% - 100% in 0.1% Increments
- Highly Accurate
- Measurement results achieved quickly
- Integrated data logging: 10,000+ measurements stored
- Adjustable alarm feature with pass/fail indicator
- Integrated Safety holster for probe & needle
- Selectable Operator I.D. & Production Line Numbers
- Programmable Product Profiles with full reporting of information for traceability
- Multiple Languages Loaded on Device
- No PC Software Required
- Standard dual-use USB cable for charging and data transfer to PC
- Easy to Use
- Low Cost of Ownership
- Holds Calibration for 1 year
- High Capacity Lithium Battery
- Programmable Auto-Shutdown function to save power
- Modular design with easy to replace tubing and fittings
- Upgraded Hydrophobic Filter
- Internal filter for additional protection for sensor array
- New Faster CO₂ sensor
- Purge Function for clearing the sample path
- Bluetooth® Connectivity
- Wi-Fi Enabled.

AGC
INSTRUMENTS

Gas Chromatography since 1965



www.agc-instruments.com

Principle Of Operation

The Map-Pak 2, using a small gas sample from the gas flushed pack, measures, and records levels of Oxygen (O₂) or Oxygen and Carbon Dioxide (CO₂). The levels of gas are measured using specially customised sensors; Oxygen levels are measured by an electrochemical sensor and the Carbon Dioxide levels are measured by a nondispersive infrared sensor (NDIR). An electric pump automatically draws the gas sample from the food packaging via the sample probe into the sensor array. The O₂ and CO₂ particles are detected by the respective sensors and the measurements are displayed on the screen within seconds. The N₂ level is then displayed as a balance gas (BAL) reading (e.g. 100% - (%O₂ + %CO₂)).

Key Features

- Lightweight & Portable
- Fast and Accurate O₂ & CO₂ readings
- Easy to use interface
- Minimal gas sample required
- Holds Calibration for one year
- Modular probe design with easy to replace parts
- Long Battery Life / Alternative mains power supply
- Sample Flow sensor for Needle blockage alarm



Results and Reporting

Results can be stored on the Map-Pak device and can be downloaded to a computer as a CSV (Excel) file using the USB cable provided. Furthermore, a small portable printer is available for the Map-Pak range to print results on receipt-size paper or labels. The Map-Pak 2 communicates wirelessly via Bluetooth® with this compact printer using special thermal paper which means that no ink cartridges are used, thereby cutting down on costs. The fast print speed ensures that results are printed promptly for your record keeping needs with a fine cutter to separate the records easily. Each of these reporting options allows the user to display their results in a way that best suits their HACCP system. Furthermore, the calibration certificates provided with each Map-Pak unit adheres to the Modified Atmosphere Packaging and HACCP requirements for audits.

Calibration

The Map-Pak 2 analyser requires an annual calibration only. There is an Ambient Calibration function available to the user to check the analyser using an air sample (O₂ being 20.9% typically).

A reminder will appear on the screen when the annual calibration is due and this can be carried out by AGC Instruments or your local Distributor. This involves calibrating the Map-Pak 2 analysers against certified gas mixtures and full support is provided to each distributor with spare parts always maintained in stock.

Typical Applications

- Meat and Poultry
- Seafood
- Pre-cooked Meats
- Dairy Produce
- Fruits & Vegetables
- Convenience Foods
- Baked Goods
- Salads
- Pasta
- Coffee
- Pharmaceuticals
- Glove Box Analysis



Specifications	
Accuracy	O ₂ ± 1% (full scale) / CO ₂ ± 5% (of reading e.g. 20% CO ₂ = Accuracy of ± 1%)
Accuracy at 1% O ₂ & 20% CO ₂	Better than ± 0.25% O ₂ and Better than ± 1% CO ₂
Resolution	0.1%
Repeatability	1% relative to gas reading
Measurement Methods	Electro Chemical Sensor (O ₂) & Nondispersive Infrared Sensor (CO ₂)
Measurement Range	0% to 100% in 0.1% increments
Operating Temperature	0 to +40 Degrees Celsius
Response Time	<20 seconds
Sensor Lifetime	O ₂ Sensor - 2 years* CO ₂ Sensor - Indefinitely
Sample Gas Volume Options	Low, Medium & High
Sample Inlet Fitting	Sturdy Nickel Plated Brass Bulkhead Connector for tubing connection
Sample Probe Fittings	User replaceable and modular design with flexible PVC Tubing
Filters	External Hydrophobic Filter & Internal Inline Filter to protect Sensor Array
Product Profiles	20 Programmable Product Profiles combined with Operator ID's and Line Numbers
Sampling Function	One button to begin sampling and automatic display of results
Purge Function	Double press button to clear sample path with larger volume of a new gas mixture
Alarms	Customisable High & Low Alarms for both O ₂ and CO ₂ readings for each Product Profile
Calibration Interval	Once a year. Ambient Calibration option available for customer check if required.
User Interface	3.5" Colour Touch Screen Display
Data Storage	10,000+ Measurements stored internally on high capacity SD card
Data Output - PC	USB Cable (Type A Plug to Micro Type B Plug) provided Download results to CSV file (Excel) with no software required Wi-Fi Enabled
Data Output - Thermal Printer	Bluetooth® connection to Thermal Printer for automatic print-outs of results
Power Supply	USB Charger, 5V 2.1A with Universal AC Supply
Battery	Rechargeable Lithium Polymer High-Capacity Battery - 2500 mAh
Operation Time	8 Hours typically (depending on usage)
Power Saver Function	User defined auto-shutdown feature to conserve battery life (can be turned off also)
Enclosure	ABS plastic with recessed probe holder (Wipe-clean, Strong and light-weight)
Dimensions	190 (L) x 79 (W) x 47 (D) mm
Weight	Combi Model: 367g / O ₂ Model: 337g
Approvals	CE - according to EMC 2004/108/EC, Low Voltage Directive 2006/95/EC and EN300328 Manufactured under the auspices of ISO 9001:2015 Quality Management System
Accessories Provided (as standard with each unit)	Needles (5), Septa (100), Hydrophobic Filters (3), Bench Mount Carry Case (1 off), USB Cable (1), Universal Mains Adapter (1), User Manual (1) & Calibration Certificate (1).

*Higher O₂ levels in food packaging may decrease this time depending on the concentration.





Company Profile

AGC Instruments Ltd.

AGC Instruments is a leading manufacturer of Gas Analysis Solutions to all users requiring a Quality Control or identification of their gas stream. We have over 59 years of experience in providing our customers with quality control solutions and work closely with all customers to ensure they obtain the analytical solution that meets their needs and a system that is easy to use and understand. All AGC distributors are extremely experienced and factory trained to the highest standards, offering you a complete after sales support service.

We place an emphasis on the continuous development of our analytical solutions and our worldwide reach with strategic partners ensures that you have peace of mind and after sales care that are important to your operations.



Proven Technology


Precision

Guaranteed Applications

Flexible & Versatile Solutions

High Sensitivity Analysis

© 2024 by AGC Instruments Ltd.
All rights reserved. No part of this document may be reproduced or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission of AGC Instruments Ltd. Due to our company policy of continual development all specifications are subject to change without notice.



Aftersales Care

AGC Instruments are committed to providing and maintaining quality products. We believe that our After Sales Support to the customer is one of the most important services we can offer. Each Distributor has been carefully selected and trained to ensure our customers receive the best possible service. Furthermore, online customer support and direct support are available to deliver a comprehensive support package.

For further information please contact:

AGC Headquarters

Unit 2, Shannon Free Zone West,
Shannon, Co. Clare, V14 PX03, Ireland.
T: +353 61 471632 F: +353 61 471042
E: sales@agc-instruments.com

www.agc-instruments.com



Sintech Scientific (S.E.A.) Pte Ltd
No. 194 Pandan Loop #04-11
Pantech Business Hub
Singapore 128383
Tel : 65-67790007
Fax : 63520877, 63520885
Email : sales@sintechscientific.com
Website : www.sintechscientific.com